

Technical Data Sheet

Eicoat LIME PLASTER

Effective From	21 Sep, 2020
-----------------------	--------------

Eiwood Lime Plaster is a fine-grained lime plaster for internal or external use. Eiwood Lime Plaster can be tinted to a wide range of colours using alkali resistant mineral pigments to achieve a range of natural colours and attractive patina effects. This versatile plaster can be used to create a wide range of finishes, from a the classic float finish to artisanal finish techniques.

Features

- Contains no added Portland Cement.
- Zero VOC.
- Can be tinted to a wide range of colours (some fading will occur depending on pigments used).
- Develops a unique patina, unrivalled by modern coatings.

Benefits

- Many different styles of finish can be achieved using different trowels, floats, sponges and finishing techniques.
- Extremely durable.
- Low to no odour or residual off-gassing.

Uses

- Suitable for interior and exterior use.
- Suitable for the refurbishment and repair of heritage listed and architecturally sensitive buildings.
- Can be applied over any standard building substrate following correct surface preparation.

Colours and Gloss

- Off-white to white colour.
- Can be tinted to a wide range of colours using alkali resistant oxides.
- ROCKCOTE recommends not exceeding 4% of product weight in oxide addition.
- Fading may occur depending on type of pigment used.

Sheen Level	Flat finish
Coverage Rate	5m ² /18kg bag @ 3mm thickness
Application Method	Stainless Steel Trowel
Dry Film Build	2 - 4mm
Wet Film Build	

Typical Data at 25oC and 50% Relative Humidity

Drying Time	8 hours
Touch Dry	8 hours
Curing Time	28 days
Usual No Coats	1 to 2
Clean Up	Water
Packaging Sizes	18Kgs
Abrasion Resistance	Very Good
Water Resistance	Excellent
Pot Life	4 hours